



- no button operation
- flexible media
up to 1 mm thickness
- measurements of transmissive
and reflective media

Spectro Swing

Thanks to his ability to measure also transparent materials and to measure most different flexible media, the Spectro Swing is a very special and unique measurement device. It is the ideal measurement device for production environments as it is tailored to the needs of all aqueous, solvent and UV roll-to-roll printers.

Application fields

- Creation of ICC profiles for digital output devices for most different materials (both reflective and transparent)
- Linearization of digital output devices
- Single measurements of spot-colors with subsequent check of the color-true printing

Target markets

- Inkjet (aqueous, solvent) printing
- Digital photo printing
- Packaging











Main features

- For transparent and reflective media
- Measurement aperture diameter 2 mm
- Easy to use thanks "no-button operation"
- Able to measure targets with up to 3000 patches

- For most different, flexible media up to 1 mm thickness (paper, banner, canvas, canvas cover for trucks, backlit, etc.)
- Supported by most RIP-software (www.barbierielectronic.com)
- ISO 13655-2009 measurement conditions: M0, M2 (UVCut)
- Including free measurement software Barbieri Gateway for Mac and PC
- Geometry:
 - reflection 45°/0°
 - transmission d/0°

System requirements

- Microsoft Windows XP or later (32 and 64 bit)
- Mac OS X 10.5 or later (Intel)

	Spectro Swing
 2 mm measuring aperture	
 Up to 1 mm thick media	
 Automatic measurements	
 Reflective measurements	
 Transmissive measurements	

Accessories Spectro Swing

